



K-STYLE OPTIGRIP WALK SURFACE LOAD TABLE
 12 GA SST, 1.50" Depth

3-ROW / 5.27" WIDTH							
	SPAN						
	2'-0"	2'-6"	3'-0"	3'-6"	4'-0"	4'-6"	5'-0"
U	1123	789	548	402	308	243	197
D	0.041	0.064	0.092	0.126	0.164	0.208	0.257
C	1233	986	882	704	616	548	493
D	0.032	0.051	0.074	0.100	0.131	0.166	0.205

5-ROW / 7.64" WIDTH							
	SPAN						
	2'-0"	2'-6"	3'-0"	3'-6"	4'-0"	4'-6"	5'-0"
U	1257	804	558	410	314	248	201
D	0.039	0.061	0.088	0.120	0.157	0.199	0.246
C	1257	1006	838	718	628	558	503
D	0.031	0.049	0.070	0.096	0.126	0.159	0.197

7-ROW / 10.02" WIDTH							
	SPAN						
	2'-0"	2'-6"	3'-0"	3'-6"	4'-0"	4'-6"	5'-0"
U	1269	812	564	414	317	520	203
D	0.038	0.060	0.086	0.118	0.154	0.195	0.241
C	1269	1015	846	725	634	564	507
D	0.030	0.166	0.069	0.094	0.123	0.156	0.192

9-ROW / 12.39" WIDTH							
	SPAN						
	2'-0"	2'-6"	3'-0"	3'-6"	4'-0"	4'-6"	5'-0"
U	1056	676	469	345	264	208	169
D	0.037	0.058	0.084	0.114	0.149	0.189	0.234
C	1056	845	704	603	528	469	422
D	0.029	0.046	0.067	0.091	0.119	0.151	0.187

U = safe uniform load in lb/sq-ft. Ex: Pedestrian traffic, multiple container stacks.
 C = safe concentrated load in lb/ft at mid span. Ex: Equipment legs, single container stack.
 D = deflection in inches.